

## P/N MS24665-237

### **Description**

corrosion resistant steel - 5/64" diameter - 1-3/4" length - cotter pin

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS24665237

Minimum Qty (MOQ): 100

NSN: 5315-00-959-6921

National Motor Freight: 094380, Cotter Pins / Spring Cotters Iron



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24665-237 Specifications

Diameter:	0.072 Inches Minimum And 0.076 Inches Maximum
Underloop Length:	1.625 Inches Minimum And 1.875 Inches Maximum
Point Type:	Extended Prong Square Cut
Hardness Rating:	60.0 Rockwell Superficial 15-n Minimum Overall And 70.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Standard

## **How to Order**

Order this cotter pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/cotter+pins/MS24665-237">https://military-fasteners.com/pins/cotter+pins/MS24665-237</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/cotter+pins/MS24665-237">https://military-fasteners.com/pins/cotter+pins/MS24665-237</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/cotter+pins/MS24665-237">https://military-fasteners.com/pins/cotter+pins/MS24665-237</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/pins/cotter+pins/MS24665-237">https://military-fasteners.com/pins/cotter+pins/MS24665-237</a> and selecting the quantity you want then