

**Description**

diameter: 3/32", length: 3/4", corrosion resistant steel, MS24665 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS24665300
Minimum Qty (MOQ):	100
NSN:	5315-00-234-1863
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	094380, Cotter Pins / Spring Cotters Iron



\* See page 2 for technical characteristics

## P/N MS24665-300 Specifications

<b>Diameter:</b>	0.086 Inches Minimum And 0.090 Inches Maximum
<b>Underloop Length:</b>	0.688 Inches Minimum And 0.875 Inches Maximum
<b>End Item Identification:</b>	W/s: Stream (std. Tensioned Replenishment At Sea Method); Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Shipboard Material Handling Equipment (mhe); Trainer, B-1b Aircraft; Aircraft, Airlifter C-17a; Aircraft, Eagle F-15; Aircraft, Hx Unique; Support Equipment, B-1 Aircraft; Airborne Mobile Dir Air Spt Ctl (2id), (02m Jul83) (an/uyq-3a); Fire Pumps;hemtt Family (heavy Expanded Mobility Tactical Trucks)
<b>Point Type:</b>	Extended Prong Mitre End
<b>Hardness Rating:</b>	60.0 Rockwell Superficial 15-n Minimum Overall And 70.0 Rockwell Superficial 15-n Maximum Overall
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 304 Overall
<b>Material Document And Classification:</b>	Astm A493 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Astm A380 Assn Std Single Treatment Response Overall
<b>Style Designator:</b>	Standard
<b>Departure From Cited Designator:</b>	As Modified By Point Style

## How to Order

Order this cotter pin from our inventory online by visiting <https://military-fasteners.com/pins/cotter+pins/MS24665-300> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.