

**Description**

diameter: 3/32", length: 3/4", corrosion resistant steel, MS24665 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS24665300
Minimum Qty (MOQ):	100
NSN:	5315-00-234-1863
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	094380, Cotter Pins / Spring Cotters Iron



# P/N MS24665-300 Specifications

Diameter:	0.086 Inches Minimum And 0.090 Inches Maximum
Underloop Length:	0.688 Inches Minimum And 0.875 Inches Maximum
End Item Identification:	W/s: Stream (std. Tensioned Replenishment At Sea Method); Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Shipboard Material Handling Equipment (mhe); Trainer, B-1b Aircraft; Aircraft, Airlifter C-17a; Aircraft, Eagle F-15; Aircraft, Hx Unique; Support Equipment, B-1 Aircraft; Airborne Mobile Dir Air Spt Ctl (2id), (02m Jul83) (an/uyq-3a); Fire Pumps;hemtt Family (heavy Expanded Mobility Tactical Trucks)
Point Type:	Extended Prong Mitre End
Hardness Rating:	60.0 Rockwell Superficial 15-n Minimum Overall And 70.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Standard
Departure From Cited Designator:	As Modified By Point Style

## How to Order

Order this cotter pin from our inventory online by visiting <https://military-fasteners.com/pins/cotter+pins/MS24665-300> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.