

Description

corrosion resistant steel, 3/32" diameter, 3" length, cotter pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN381-3-48](#)

SKU / Model:

MS24665312

Minimum Qty (MOQ):

50

NSN:

5315-00-543-3696

ECCN:

EAR99

National Motor Freight:

095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS24665-312 Specifications

Diameter:	0.086 Inches Minimum And 0.090 Inches Maximum
Underloop Length:	2.875 Inches Minimum And 3.125 Inches Maximum
Point Type:	Extended Prong Square Cut
Hardness Rating:	60.0 Rockwell Superficial 15-n Minimum Overall And 70.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Standard

How to Order

Order this cotter pin from our inventory online by visiting <https://military-fasteners.com/pins/cotter+pins/MS24665-312> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.