

P/N MS24665-368

Description

diameter: 1/8", length: 3/4", corrosion resistant steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS24665368

Minimum Qty (MOQ): 100

NSN: 5315-00-236-8357

ECCN: EAR99

National Motor Freight: 094380, Cotter Pins / Spring Cotters Iron









^{*} See page 2 for technical characteristics

P/N MS24665-368 Specifications

Diameter:	0.116 Inches Minimum And 0.120 Inches Maximum
Underloop Length:	0.688 Inches Minimum And 0.875 Inches Maximum
End Item Identification:	3990-01-443-8024 Engineering Mission Module Used On The Palletized Loading System
Point Type:	Extended Prong Square Cut
Hardness Rating:	55.0 Rockwell Superficial 15-n Minimum Overall And 67.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Standard

How to Order

Order this cotter pin from our inventory online by visiting https://military-fasteners.com/pins/cotter+pins/MS24665-368 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.