

## P/N MS24665-378

### **Description**

Diameter: 7/64", steel comp

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS24665378

Minimum Qty (MOQ): 50

NSN: 5315-00-899-4118

ECCN: EAR99

National Motor Freight: 094380, Cotter Pins / Spring Cotters Iron



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24665-378 Specifications

Diameter:	0.116 Inches Minimum And 0.120 Inches Maximum
Underloop Length:	2.125 Inches Minimum And 2.375 Inches Maximum
Point Type:	Extended Prong Square Cut
Hardness Rating:	55.0 Rockwell Superficial 15-n Minimum Overall And 67.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Standard

## **How to Order**

Order this cotter pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/cotter+pins/MS24665-378">https://military-fasteners.com/pins/cotter+pins/MS24665-378</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.