

Description

MS24665 series pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS24665445
Minimum Qty (MOQ):	50
NSN:	5315-00-236-8374
ECCN:	EAR99
National Motor Freight:	094380, Cotter Pins / Spring Cotters Iron



* See page 2 for technical characteristics

P/N MS24665-445 Specifications

Diameter:	0.146 Inches Minimum And 0.150 Inches Maximum
Underloop Length:	2.125 Inches Minimum And 2.375 Inches Maximum
Point Type:	Extended Prong Square Cut
Hardness Rating:	55.0 Rockwell Superficial 15-n Minimum Overall And 67.0 Rockwell Superficial 15-n Maximum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response Overall
Style Designator:	Standard

How to Order

Order this cotter pin from our inventory online by visiting <https://military-fasteners.com/pins/cotter+pins/MS24665-445> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.