

P/N MS24665-518

Description

MS24665-518 Cotter Pin

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS24665518

Minimum Qty (MOQ): 10

NSN: 5315-00-243-1171

ECCN: EAR99

National Motor Freight: 094380, Cotter Pins / Spring Cotters Iron



^{*} See page 2 for technical characteristics

P/N MS24665-518 Specifications

| Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
|--|---|
| Underloop Length: | 2.375 Inches Minimum And 2.625 Inches Maximum |
| Point Type: | Extended Prong Square Cut |
| Hardness Rating: | 55.0 Rockwell Superficial 15-n Minimum Overall And 67.0 Rockwell Superficial 15-n Maximum Overall |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall |
| Material Document And Classification: | Astm A493 Assn Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Astm A380 Assn Std Single Treatment Response Overall |
| Style Designator: | Standard |

How to Order

Order this cotter pin from our inventory online by visiting https://military-fasteners.com/pins/cotter+pins/MS24665-518 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.