

Description

Fastener Length: 41/64", Thread: 8-32, Head Width: 3/32", Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2466715L
Minimum Qty (MOQ):	45 EA
NSN:	5305-01-499-7919
Schedule B:	7318.15.2010
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS24667-15L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.497 Inches Minimum And 0.529 Inches Maximum
Fastener Length:	0.609 Inches Minimum And 0.641 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.311 Inches Minimum And 0.359 Inches Maximum
Locking Feature:	Strip Threads Or Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.0937 Inches Minimum And 0.0947 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24667-15L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.