

Description

Fastener Length: 41/64", Thread: 8-32, Head Width: 3/32", Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS2466715L |
| Minimum Qty (MOQ): | 45 EA |
| NSN: | 5305-01-499-7919 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N MS24667-15L Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.497 Inches Minimum And 0.529 Inches Maximum |
| Fastener Length: | 0.609 Inches Minimum And 0.641 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.311 Inches Minimum And 0.359 Inches Maximum |
| Locking Feature: | Strip Threads Or Patch Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.164 Inches |
| Width Across Flats: | 0.0937 Inches Minimum And 0.0947 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Countersink Angle: | 82.0 Degrees Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24667-15L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.