

## Description

Fastener Length: 3/4", Thread: 1/4-20, Head Width: 1/8", Thread Length: 21/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS2466730Z
Minimum Qty (MOQ):	5
NSN:	5305-01-380-0847
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS24667-30Z Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.666 Inches Minimum
<b>Fastener Length:</b>	0.750 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.480 Inches Minimum And 0.531 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>End Item Identification:</b>	Mrap Rg-33
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Width Across Flats:</b>	0.156 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	130000 Pounds Per Square Inch
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 84.0 Degrees Maximum
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Zinc Overall
<b>Surface Treatment Document And Classification:</b>	Qq-z-325, Ty li, Cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24667-30Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.