

Description

Fastener Length: 1", Thread: 1/4-20, Head Width: 1/8", Thread Length: 31/32", MS24667 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2466731 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-081-6728 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24667-31 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.984 Inches Minimum |
| Fastener Length: | 1.000 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.480 Inches Minimum And 0.531 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.156 Inches Nominal |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 84.0 Degrees Maximum |
| Material: | Steel Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24667-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.