

Description

Fastener Length: 63/64", Thread: 3/8-16, Head Width: 7/32", Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2466752L
Minimum Qty (MOQ):	100
NSN:	5305-01-197-1368
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24667-52L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.611 Inches Minimum And 0.736 Inches Maximum
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.720 Inches Minimum And 0.781 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.219 Inches Nominal
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	4 Type

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24667-52L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.