

Description

Fastener Length: 17/64", Thread: 6-32, Head Width: 1/16", Thread Length: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS246677Z
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-555-6620
Schedule B:	7318.15.2010
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS24667-7Z Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.137 Inches Minimum And 0.169 Inches Maximum
Fastener Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.263 Inches Minimum And 0.307 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.078 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Zinc Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24667-7Z> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.