

Description


Fastener Length: 1/2", Thread: 6-32, Head Width: 5/64", Thread Length: 13/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS246679
Minimum Qty (MOQ):	10
NSN:	5305-00-068-5396
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24667-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.387 Inches Minimum And 0.419 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.263 Inches Minimum And 0.307 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.0781 Inches Minimum And 0.0791 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24667-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.