

**Description**

Fastener Length: 0-63/64", Thread: 1/4-28, Head Width: 5/32", Thread Length: 1-"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2466813L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-424-9416
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS24668-13L Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	C1.000 Single Through Hole With Threaded Insert Nominal
<b>Fastener Length:</b>	0.984 Inches Minimum And 1.016 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.359 Inches Minimum And 0.411 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Width Across Flats:</b>	0.1562 Inches Minimum And 0.1582 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 84.0 Degrees Maximum
<b>Special Features:</b>	Ms24669 Is A Cancelled Spec
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416-ty 2, Cl 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24668-13L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.