

Description


Length: 17/64", Thread: 4-40, Head Width: 1/16", Thread Length: 11/64", MS24671 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS246711
Minimum Qty (MOQ):	25
NSN:	5305-00-144-0344
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24671-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.101 Inches Minimum And 0.183 Inches Maximum
Fastener Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.218 Inches Minimum And 0.255 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.063 Inches Nominal
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	4 Type

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24671-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.