

Description

MS24671-17 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2467117
Minimum Qty (MOQ):	10
NSN:	5305-01-274-9812
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24671-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.376 Inches Minimum And 1.814 Inches Maximum
Fastener Length:	2.920 Inches Minimum And 3.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.781 Inches Minimum And 0.844 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.438 Inches
Width Across Flats:	0.250 Inches Nominal
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell C Minimum Overall
Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Material:	Steel Comp 302 Overall Or Steel Comp 384 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	Astm A493 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	4 Type

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24671-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.