

P/N MS24671-19

Description

Fastener Length: 23/64", Thread: 10-24, Head Width: 5/32", Thread Length: 15/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2467119

Minimum Qty (MOQ): 20

NSN: 5305-00-983-6573


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS24671-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.232 Inches Minimum And 0.264 Inches Maximum
Fastener Length:	0.359 Inches Minimum And 0.391 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.359 Inches Minimum And 0.411 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.158 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24671-19 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.