

**Description**

Fastener Length: 3/4", Thread: 1/4-20, Head Width: 1/8", Thread Length: 21/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS2467130                                 |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5305-00-988-7794                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS24671-30 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.666 Inches Maximum   |
| <b>Fastener Length:</b>                               | 0.750 Inches Nominal   |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.480 Inches Minimum And 0.531 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Width Across Flats:</b>                            | 0.156 Inches Nominal   |
| <b>Thread Quantity Per Inch:</b>                      | 20   |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall  |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch   |
| <b>Countersink Angle:</b>                             | 80.0 Degrees Minimum And 84.0 Degrees Maximum  |
| <b>Material:</b>                                      | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Overall  |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unc  |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24671-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.