

Description

Fastener Length: 63/64", Thread: 1/4-20, Head Width: 1/8", Thread Length: 27/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2467131
Minimum Qty (MOQ):	10
NSN:	5305-00-938-7827
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24671-31 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.773 Inches Minimum And 0.855 Inches Maximum
Fastener Length:	0.984 Inches Minimum And 1.016 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.480 Inches Minimum And 0.531 Inches Maximum
Internal Drive Style:	Hexagon
iii End Item Identification:	Mrap - Cougar
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.156 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	4 Type

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24671-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.