

P/N MS24671-4

Description

Fastener Length: 5/8", Thread: 4-40, Thread Length: 9/16", MS24671 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS246714

Minimum Qty (MOQ): 50

NSN: 5305-00-947-6976

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS24671-4 Specifications

Thread Direction: Thread Length: 0.591 Inches Maximum Fastener Length: 0.625 Inches Nominal Head Style: Flat Countersunk Head Diameter: 0.218 Inches Minimum And 0.255 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.062 Inches Nominal Thread Quantity Per Inch: Minimum Tensile Strength: 80000 Pounds Per Square Inch	Thread Class:	3a
Thread Length: 0.591 Inches Maximum Fastener Length: 0.625 Inches Nominal Head Style: Flat Countersunk Head Diameter: 0.218 Inches Minimum And 0.255 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.662 Inches Nominal Thread Quantity Per Inch: 40 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Seel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: 9c-35 Fed Spec Single Treatment Response Overall		
Fastener Length: Head Style: Flat Countersunk Head Diameter: 0.218 Inches Minimum And 0.255 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.062 Inches Nominal Thread Quantity Per Inch: Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80000 Pounds Per Square Inch Countersink Angle: 80000 Pounds Per Square Inch Overall Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 315 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Oq-p-35 Fed Spec Single Treatment Response Overall		
Head Style: Flat Countersunk Head Diameter: 0.218 Inches Minimum And 0.255 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.062 Inches Nominal Thread Quantity Per Inch: 40 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: 0q-p-35 Fed Spec Single Treatment Response Overall	Inread Length:	0.591 Inches Maximum
Head Diameter: Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.062 Inches Nominal Thread Quantity Per Inch: 40 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: 80.0 Degrees Minimum And 84.0 Degrees Maximum Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Fastener Length:	0.625 Inches Nominal
Internal Drive Style: Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.062 Inches Nominal Thread Quantity Per Inch: 40 Minimum Tensile Strength: 40 Minimum Tensile Strength: 40 Minimum Yield Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Q-p-35 Fed Spec Single Treatment Response Overall	Head Style:	Flat Countersunk
Nominal Thread Diameter: Width Across Flats: 0.062 Inches Nominal Thread Quantity Per Inch: 40 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Head Diameter:	0.218 Inches Minimum And 0.255 Inches Maximum
Width Across Flats: 0.062 Inches Nominal Thread Quantity Per Inch: 40 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Hexagon
Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.112 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Width Across Flats:	0.062 Inches Nominal
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	40
Minimum Yield Strength: Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle: 80.0 Degrees Minimum And 84.0 Degrees Maximum Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Minimum Yield Strength:	30000 Pounds Per Square Inch
Material: Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Surface Treatment: Surface Treatment Document And Classification: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Material Document And Classification:	66 Fed Std All Material Responses Overall
Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Treatment:	Passivate Overall
Thread Series Designator: Unc		Qq-p-35 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24671-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.