

**Description**

MS24671-40

\* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	MS2467140
Minimum Qty (MOQ):	20
NSN:	5305-00-106-6241
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS24671-40 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Minimum And 0.568 Inches Maximum
<b>Fastener Length:</b>	0.734 Inches Minimum And 0.766 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.600 Inches Minimum And 0.656 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Width Across Flats:</b>	0.188 Inches Nominal
<b>Features Provided:</b>	Casehardened
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 84.0 Degrees Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall Or Nickel Alloy Overall
<b>Material Document And Classification:</b>	Fed Std 66,302 Or 303 Or 304 Or 305 Or 316 Or Equal To 16-18 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	4 Type

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24671-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.