

Description

Fastener Length: 1-1/64", Thread: 3/8-16, Head Width: 7/32", Thread Length: 57/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2467152 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-942-2224 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS24671-52 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.891 Inches Maximum |
| Fastener Length: | 1.000 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.720 Inches Minimum And 0.781 Inches Maximum |
| Internal Drive Style: | Hexagon |
| End Item Identification: | Mrap Rg-33 |
| Nominal Thread Diameter: | 0.375 Inches |
| Width Across Flats: | 0.219 Inches Nominal |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 84.0 Degrees Maximum |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24671-52> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.