

Description

Fastener Length: 1-31/32", Thread: 3/8-16, Head Width: 7/32", Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2467156
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-191-7491
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24671-56 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum
Fastener Length:	1.960 Inches Minimum And 2.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.720 Inches Minimum And 0.781 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	Mrap Rg-33
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.219 Inches Nominal
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	4 Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24671-56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.