

**Description**

Fastener Length: 0-63/64", Thread: 1/2-13, Head Width: 1/4", Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2467174
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-990-8353
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS24671-74 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.733 Inches Minimum And 0.765 Inches Maximum
<b>Fastener Length:</b>	0.984 Inches Minimum And 1.016 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.872 Inches Minimum And 0.937 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Width Across Flats:</b>	0.312 Inches Maximum
<b>Thread Quantity Per Inch:</b>	13
<b>Minimum Tensile Strength:</b>	70000 Pounds Per Square Inch
<b>Hardness Rating:</b>	80.0 Rockwell B Minimum Overall
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Countersink Angle:</b>	82.0 Degrees Nominal
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24671-74> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.