

Description

Fastener Length: 23/64", Thread: 10-32, Head Width: 1/8", Thread Length: 9/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS246721
Minimum Qty (MOQ):	25
NSN:	5305-01-336-0051
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24672-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.281 Inches Nominal
Fastener Length:	0.359 Inches Minimum And 0.391 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.359 Inches Minimum And 0.411 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.125 Inches Minimum And 0.127 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Material:	Steel Comp 303 Overall Or Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	4 Type

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24672-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.