

# P/N MS24672-30

Military-Fasteners.com

#### Description

Fastener Length: 1-31/64", Thread: 3/8-24, Head Width: 7/32", Thread Length: 1-1/64", MS24672 series screw

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

# Order this part online

#### **Additional Information**

SKU / Model:	MS2467230
Minimum Qty (MOQ):	5
NSN:	5305-01-230-5193
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS24672-30 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Minimum
Fastener Length:	1.484 Inches Minimum And 1.531 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.720 Inches Minimum And 0.781 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.218 Inches Minimum And 0.220 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	70000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Nominal Overall
Countersink Angle:	80.0 Degrees Minimum And 84.0 Degrees Maximum
Material:	Steel Comp 303 Overall Or Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	4 Туре

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/MS24672-30</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.