

Description

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 10-24, Head Width: 11/64", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2467413
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-067-9916
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24674-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.308 Inches Nominal
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.157 Inches Nominal
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Chamfer Angle:	30.0 Degrees Minimum And 45.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24674-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.