

## P/N MS24677-12

### **Description**

length: 1", thread: 6-32, socket head, alloy steel drilled head

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS2467712

Minimum Qty (MOQ): 10

NSN: 5305-00-058-2070

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24677-12 Specifications

3a
Right-hand
0.750 Inches Minimum
1.000 Inches Nominal
Flat Chamfer
0.218 Inches Minimum And 0.226 Inches Maximum
0.134 Inches Minimum And 0.138 Inches Maximum
0.033 Inches Minimum And 0.039 Inches Maximum
Hexagon
0.138 Inches
0.109 Inches Minimum And 0.111 Inches Maximum
2
Drilled
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
130000 Pounds Per Square Inch
Round
Steel Overall
66 Fed Std Single Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Unc

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-12">https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-12">https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-12">https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-12</a> and selecting