

**Description**

Fastener Length: 2-1/4", Hole Diameter: 3/32", Thread: 3/4-10, Head Width: 5/8", Thread Length: 2-"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS24677136
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-207-1759
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS24677-136 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	2.000 Inches Minimum
<b>Fastener Length:</b>	2.250 Inches Nominal
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.741 Inches Minimum And 0.750 Inches Maximum
<b>Head Height:</b>	1.107 Inches Minimum And 1.125 Inches Maximum
<b>Hole Diameter:</b>	0.091 Inches Minimum And 0.097 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Width Across Flats:</b>	0.625 Inches Minimum And 0.631 Inches Maximum
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	10
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	130000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Hexagon Longitudinal Hole
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24677-136> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.