

Description

Fastener Length: 2-1/4", Hole Diameter: 3/32", Thread: 3/4-10, Head Width: 5/8", Thread Length: 2-"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24677136
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-207-1759
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24677-136 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.000 Inches Minimum
Fastener Length:	2.250 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.741 Inches Minimum And 0.750 Inches Maximum
Head Height:	1.107 Inches Minimum And 1.125 Inches Maximum
Hole Diameter:	0.091 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.750 Inches
Width Across Flats:	0.625 Inches Minimum And 0.631 Inches Maximum
Hole Type:	Drilled
Thread Quantity Per Inch:	10
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24677-136> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.