

P/N MS24677-15

Description

length: 1/2", thread: 8-32, socket head, alloy steel, drilled head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2467715

Minimum Qty (MOQ): 10

NSN: 5305-00-969-6503

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS24677-15 Specifications

Thread Class: Signature of Might-hand Signature of Mig		
Thread Length: 0.500 Inches Minimum Fastener Length: 0.500 Inches Nominal Head Style: Flat Chamfer Head Diameter: 0.262 Inches Minimum And 0.270 Inches Maximum Head Height: 0.599 Inches Minimum And 0.164 Inches Maximum Head Height: 0.044 Inches Minimum And 0.164 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.164 Inches Width Across Flats: 0.141 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Quantity: 0.164 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 0.164 Inches Minimum And 0.143 Inches Maximum Hole Quantity Per Inch: 0.184 Hole Thread Quantity Per Inch: 0.184 Hardness Rating: 0.184 Hardness Rating: 0.185 Hole Configuration Style: 0.185 Hole Configuration Style: 0.185 Hole Configuration Style: 0.185 Hole Configuration Style: 0.185 Haterial Document And Classification: 0.185 Haterial Document And Classification: 0.185 Hole Cambium Overall And Chromate Overall Surface Treatment: 0.29-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Class:	3a
Fastener Length: 0.500 Inches Nominal Head Style: Flat Chamfer Head Diameter: 0.262 Inches Minimum And 0.270 Inches Maximum Head Height: 0.159 Inches Minimum And 0.164 Inches Maximum Hole Diameter: 0.044 Inches Minimum And 0.050 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.164 Inches Width Across Flats: 0.141 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Round Longiturial Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Ocument And Classification: 9q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Direction:	Right-hand
Head Style: Head Diameter: Head Diameter: Head Height: Hole Diameter: Hole Olameter: Hole Quantity: Hole Quantity: Hole Type: Hole Quantity Per Inch: Hole Quantity Per Inch: Hole Quantity Per Inch: Hole Olameter: Hol	Thread Length:	0.454 Inches Minimum
Head Diameter: 0.262 Inches Minimum And 0.270 Inches Maximum Head Height: 0.159 Inches Minimum And 0.164 Inches Maximum Hole Diameter: 0.044 Inches Minimum And 0.050 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.141 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Q-q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Fastener Length:	0.500 Inches Nominal
Head Height: Hole Diameter: 10.044 Inches Minimum And 0.164 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.141 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hoffware Stating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Longitudinal Hole Material: Material Document And Classification: Surface Treatment: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Style:	Flat Chamfer
Hole Diameter: 0.044 Inches Minimum And 0.050 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.141 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Internal Drive Style: Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.141 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 9q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Nominal Thread Diameter: Width Across Flats: 0.141 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: Gadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Width Across Flats: Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: H30000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Internal Drive Style:	Hexagon
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.164 Inches
Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: Minimum Yield Strength: Minimum Yield Strength: Hole Configuration Style: Material: Material: Material Document And Classification: Surface Treatment: Drilled 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Overall And 43.0 Rockwell C Maximum Overall Maximum Overall And 43.0 Rockwell C Maximum Overall Maximum Overall And 43.0 Rockwell C Maximum Overall And Longitudinal Hole Steel Overall Material Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch 130000 Pounds Per Square Inch Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Quantity:	6
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	32
Minimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style: Material: Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Configuration Style:	Round Longitudinal Hole
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unc	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.