

P/N MS24677-16

Description

length: 5/8", thread: 8-32, socket head, alloy steel drilled head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS2467716

Minimum Qty (MOQ): 20

NSN: 5305-00-812-8503

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS24677-16 Specifications

Thread Direction: Right-hand Thread Length: 0.533 Inches Minimum And 0.625 Inches Maximum Fastener Length: 0.595 Inches Minimum And 0.625 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.262 Inches Minimum And 0.270 Inches Maximum Head Height: 0.159 Inches Minimum And 0.270 Inches Maximum Head Height: 0.159 Inches Minimum And 0.164 Inches Maximum Hole Diameter: 0.044 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.140 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment Document And Classification: 9q-p-416,type 2, class 3 Fed Spec Single Treatment Response Overall		
Thread Length: 0.533 Inches Minimum And 0.625 Inches Maximum Fastener Length: 0.595 Inches Minimum And 0.625 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.262 Inches Minimum And 0.270 Inches Maximum Head Height: 0.159 Inches Minimum And 0.164 Inches Maximum Hole Diameter: 0.044 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.140 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material Document And Classification: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Oq-p-416, type 2, class 3 Fed Spec Single Treatment Response Overall	Thread Class:	3a
Fastener Length: Head Style: Flat Chamfer Head Diameter: Head Height: Hole Diameter: Nominal Thread Diameter: Nominal Thread Diameter: Width Across Flats: Width Across Flats: Width Across Flats: Width Across Flats: Wildth Across Flats	Thread Direction:	Right-hand
Head Style: Head Diameter: O.262 Inches Minimum And 0.270 Inches Maximum Head Height: O.159 Inches Minimum And 0.164 Inches Maximum Hole Diameter: O.044 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: O.164 Inches Width Across Flats: O.140 Inches Minimum And 0.143 Inches Maximum Hole Quantity: Official Company of the Maximum Hole Quantity: Official Company of the Maximum Hole Quantity Per Inch: Official Company of the Maximum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Official Configuration Style: Material Document And Classification: Official Company of the Maximum Overall Material Response Overall Surface Treatment: Oq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Thread Length:	0.533 Inches Minimum And 0.625 Inches Maximum
Head Diameter: Head Height: O.262 Inches Minimum And 0.270 Inches Maximum O.159 Inches Minimum And 0.164 Inches Maximum Hole Diameter: O.044 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: O.164 Inches Width Across Flats: O.140 Inches Minimum And 0.143 Inches Maximum Hole Quantity: Orilled Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: Minimum Tensile Strength: Hardness Rating: Minimum Yield Strength: Hole Configuration Style: Round Longitudinal Hole Material: Material Document And Classification: Oq-p-416.type 2.class 3 Fed Spec Single Treatment Response Overall	Fastener Length:	0.595 Inches Minimum And 0.625 Inches Maximum
Head Height: Hole Diameter: O.044 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: O.164 Inches Width Across Flats: O.140 Inches Minimum And 0.143 Inches Maximum Hole Quantity: Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: Minimum Yield Strength: Hole Configuration Style: Mone Configuration Style: Material Material Document And Classification: Ge Fed Std Single Material Response Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Head Style:	Flat Chamfer
Hole Diameter: 0.044 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.164 Inches Width Across Flats: 0.140 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Qq-p-416.type 2,class 3 Fed Spec Single Treatment Response Overall	Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Internal Drive Style:HexagonNominal Thread Diameter:0.164 InchesWidth Across Flats:0.140 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:180000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Nominal Thread Diameter: Width Across Flats: 0.140 Inches Minimum And 0.143 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 18000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Hole Diameter:	0.044 Inches Nominal
Width Across Flats: Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Hexagon
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: Gef Fed Std Single Material Response Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.164 Inches
Hole Type: Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: Minimum Yield Strength: Minimum Yield Strength: Minimum Yield Strength: Mound Longitudinal Hole Material: Material Document And Classification: Surface Treatment Document And Classification: Drilled 32 Material Drilled 32 Material And Chromate Overall Material Preatment Response Overall Surface Treatment Document And Classification: Drilled 32 Maximum Overall And Chromate Overall Material Sponse Overall	Width Across Flats:	0.140 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 180000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Hole Quantity:	6
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Hole Type:	Drilled
Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	32
Minimum Yield Strength: Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hole Configuration Style: Material: Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Hole Configuration Style:	Round Longitudinal Hole
Surface Treatment: Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unc	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.