

P/N MS24677-18

Military-Fasteners.com

Description

MS24677-18 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	MS2467718	
Minimum Qty (MOQ):	10	
NSN:	5305-00-273-5558	
Schedule B:	7318.15.2000	
ECCN:	EAR99	
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)	



P/N MS24677-18 Specifications

Thread Class:3aThread Direction:Right-handThread Length:0.875 Inches MinimumFastener Length:0.875 Inches Minimum And 0.270 Inches MaximumHead Style:Flat ChamferHead Diameter:0.502 Inches Minimum And 0.270 Inches MaximumHole Diameter:0.505 Inches Minimum And 0.164 Inches MaximumHole Diameter:0.505 Inches Minimum And 0.164 Inches MaximumHole Diameter:0.505 Inches Minimum And 0.164 Inches MaximumHole Diameter:0.505 Inches Minimum And 0.141 Inches MaximumNominal Thread Diameter:0.164 InchesNominal Thread Diameter:0.164 InchesHole Opantity:6Hole Opantity:6Hole Opantity:1000 Pounds Per Square InchHardness Rating:1000 Pounds Per Square InchHinimum Yield Strength:13000 Pounds Per Square InchHole Opantity:6Fed Stud Single Material Response OverallHaterial Document And Classification:6Fed Stud Single Material Response Over		
Thread Length:0.875 Inches MinimumFastener Length:0.875 Inches NominalHead Style:Flat ChamferHead Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.262 Inches Minimum And 0.170 Inches MaximumHead Height:0.59 Inches NominalHead Diameter:0.50 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.164 InchesWieth Across Flats:0.141 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Type:DirliedThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHole Configuration Style:Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHoterati:30000 Pounds Per Square InchMaterial:Steel OverallMaterial:Steel OverallMaterial:Ge Fed Stat Single Material Response OverallSurface Treatment:Ocentier And Classification:Query La Care Steel Single Treatment Response OverallSteel Overall	Thread Class:	3a
Fastener Length:0.875 Inches NominalHead Style:Flat ChamferHead Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.159 Inches Minimum And 0.164 Inches MaximumHole Diameter:0.050 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.164 Inches Minimum And 0.143 Inches MaximumWidth Across Flats:0.141 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHole Strength:30000 Pounds Per Square InchHole Corfiguration Style:Sco Rockwell C Minimum Overall And 3.0 Rockwell C Maximum OverallMaterial Document And Classification:6 Fed Std Single Material Response OverallStrafee Treatment:Cadmium Overall And Chromate OverallMaterial Document And Classification:6 Fed Std Single Material Response Overall	Thread Direction:	Right-hand
Head Style:Flat ChamferHead Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.159 Inches Minimum And 0.164 Inches MaximumHole Diameter:0.050 Inches NominalHoraral Drive Style:HexagonNominal Thread Diameter:0.164 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Quantity:0Hole Style:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHole Strength:30.0 Rockwell C Minimum Overall And 4.3.0 Rockwell C Maximum OverallHole Configuration Style:Round Internal HexagonMaterial Document And Classification:6 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:6 Fed Std Single Material Response Overall	Thread Length:	0.875 Inches Minimum
Head Diameter:0.262 Inches Minimum And 0.270 Inches MaximumHead Height:0.159 Inches Minimum And 0.164 Inches MaximumHole Diameter:0.050 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.164 InchesWidth Across Flats:0.164 Inches Maximum And 0.143 Inches MaximumHole Quantity:6Hole Quantity:Flats:Hore Quantity Per Inch:32Minimum Tensile Strength:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Round Internal HexagonHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:6 Fed Std Single Material Response OverallSurface Treatment Document And Classification:Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Fastener Length:	0.875 Inches Nominal
Head Height:0.159 Inches Minimum And 0.164 Inches MaximumHole Diameter:0.050 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.164 InchesWidth Across Flats:0.164 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHole Configuration Style:8.000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial:Steel OverallSurface Treatment:Cadmium Overall And Chassification:Surface Treatment Document And Classification:Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Head Style:	Flat Chamfer
Hole Diameter:0.050 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.164 InchesWidth Across Flats:0.141 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Qu-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Internal Drive Style:HexagonNominal Thread Diameter:0.164 InchesWidth Across Flats:0.141 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHole Configuration Style:86.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate DoverallSurface Treatment Document And Classification:0q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Nominal Thread Diameter:0.164 InchesWidth Across Flats:0.141 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:9q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Hole Diameter:	0.050 Inches Nominal
Width Across Flats:0.141 Inches Minimum And 0.143 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed St Single Material Response OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Hexagon
Hole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment Document And Classification:Qu-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.164 Inches
Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQr.p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:36.000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Hole Quantity:	6
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Hole Type:	Drilled
Hardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	32
Minimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Sti gle Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Hole Configuration Style:	Round Internal Hexagon
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unc	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-18</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.