

Description

Fastener Length: 3/8", Hole Diameter: 1/32", Thread: 4-40, Head Width: 3/32", Thread Length: 5/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS246772 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-058-2066 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS24677-2 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.341 Inches Minimum |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.176 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.108 Inches Minimum And 0.112 Inches Maximum |
| Hole Diameter: | 0.033 Inches Nominal |
| Internal Drive Style: | Hexagon |
| End Item Identification: | W/s:missile, All-weather Anti-ship, Harpoon (agm-84); Close In Weapon System (ciws-phalanx); Aircraft, Osprey V-22aa, Marine Corps; Aircraft, B-2 Bomber (atb); Aircraft. Awacs, E-3a; Aircraft, Osprey V-22a, Air Force; Aircraft, Airlifter C-17a; Engine, Aircraft F110-ge-400; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Engine, T55-ga-714a (ch-47) |
| Nominal Thread Diameter: | 0.112 Inches |
| Width Across Flats: | 0.094 Inches Minimum And 0.095 Inches Maximum |
| Hole Quantity: | 2 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Hole Configuration Style: | Round |
| Criticality Code Justification: | Agav |
| Material: | Steel Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.