

P/N MS24677-5

Description

Fastener Length: 3/4", Hole Diameter: 1/32", Thread: 4-40, Head Width: 3/32", Thread Length: 3/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS246775	
Minimum Qty (MOQ):	10 EA	
NSN:	5305-00-975-3841	
Schedule B:	7318.15.6080	
ECCN:	EAR99	
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)	



^{*} See page 2 for technical characteristics

P/N MS24677-5 Specifications

Thread Direction: Right-hand Thread Length: 0.670 Inches Minimum And 0.750 Inches Maximum Fastener Length: 0.720 Inches Minimum And 0.750 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.176 Inches Minimum And 0.181 Inches Maximum Head Height: 0.108 Inches Minimum And 0.181 Inches Maximum Head Height: 0.093 Inches Minimum And 0.181 Inches Maximum Head Height: 0.093 Inches Minimum And 0.191 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity Per Inch: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity Per Inch: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity Per Inch: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity Per Inch: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Conditive Order of the Conditive Order of Condit		
Thread Length: Fastener Length: Head Style: Head Diameter: Head Diameter: Head Height: Hoel Diameter: Hole Ognatity: Hole Quantity: Hole Quantity: Hole Quantity Per Inch: Hole Quantity Per Inch: Hole Quantity Per Inch: Hole Ognatity Pe	Thread Class:	3a
Fastener Length: 0.720 Inches Minimum And 0.750 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum Head Height: 0.033 Inches Minimum And 0.112 Inches Maximum Hole Diameter: 0.033 Inches Minimum And 0.112 Inches Maximum Hole Diameter: 0.033 Inches Minimum And 0.039 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 2.12 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 2.12 Inches Winder Type: Drilled Thread Quantity Per Inch: 4.00 Minimum Tensile Strength: 1.000 Pounds Per Square Inch Hardness Rating: 1.000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: 8.000 Pounds Per Square Inch Material: 8.000 Pounds Per Square Inch Material Document And Classification: 8.000 Pounds Per Square Inch Material Document And Classification: 9.000 Pounds Per Square Inch Surface Treatment Document And Classification: 9.000 Pounds Per Square Inch Surface Treatment Document And Classification: 9.000 Pounds Per Square Inch Surface Treatment Document And Classification: 9.000 Pounds Per Square Inch Surface Treatment Document And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds Per Square Inch Surface Treatment Pocument And Classification: 9.000 Pounds	Thread Direction:	Right-hand
Head Style: Head Diameter: Head Diameter: Head Height: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hexagon Nominal Thread Diameter: Width Across Flats: Hole Quantity: Hole Quantity: Thread Quantity Per Inch: Minimum Tensile Strength: Hard Quantity Per Inch: Minimum Tensile Strength: Hard Quantity: Hole Onfiguration Style: Minimum Yield Strength: Hole Onfiguration Style: Mound Across Flats: Hole Quantity Per Inch: Minimum Yield Strength: Hole Onfiguration Style: Mound Longitudinal Hole Material: Material Document And Classification: Material Document And Classification: Melad Style: Hexagon 1.12 Inches Maximum And 0.12 Inches Maximum 1.012 Inches Maximum 1.013 Inches Maximum And 0.095 Inches Maximum 1.014 Inches 1.015 Inches Maximum 1.016 Inches Minimum And 0.095 Inches Maximum 1.016 Inches Maximum 1.017 Inches 1.018 Inches Maximum 1.018 Inches Maximum And 0.095 Inches Maximum 1.018 Inches Ma	Thread Length:	0.670 Inches Minimum And 0.750 Inches Maximum
Head Diameter: 0.108 Inches Minimum And 0.183 Inches Maximum Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum Hole Diameter: 0.033 Inches Minimum And 0.039 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 2 Hole Type: Drilled Hole Type: Drilled Hole Type: Drilled Hinimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Q-q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Height: Hole Diameter: O.033 Inches Minimum And 0.112 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: O.112 Inches Width Across Flats: O.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: Call Diameter: Drilled Thread Quantity Per Inch: Hardness Rating: Hole Strength: Hardness Rating: Minimum Yield Strength: Hole Configuration Style: Material Document And Classification: Steel Overall Material Document And Classification: Oq.p-16,ty 2,cl 3 Fed Spec All Treatment Responses Overall Surface Treatment Document And Classification: Oq.p-16,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Style:	Flat Chamfer
Hole Diameter: 0.033 Inches Minimum And 0.039 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 2 Hole Type: Drilled Thread Quantity Per Inch: 40 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Internal Drive Style:HexagonNominal Thread Diameter:0.112 InchesWidth Across Flats:0.094 Inches Minimum And 0.095 Inches MaximumHole Quantity:2Hole Type:DrilledThread Quantity Per Inch:40Minimum Tensile Strength:180000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Nominal Thread Diameter: Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Hole Quantity: 2 Hole Type: Drilled Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 9q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Diameter:	0.033 Inches Minimum And 0.039 Inches Maximum
Width Across Flats: 10.094 Inches Minimum And 0.095 Inches Maximum 21 Hole Type: Drilled Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Internal Drive Style:	Hexagon
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 40 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.112 Inches
Hole Type: Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: Minimum Yield Strength: Minimum Yield Strength: Hole Configuration Style: Material: Material Document And Classification: Material Document And Classification: Surface Treatment Document And Classification: Drilled 40 Material Document And Classification: Drilled 40 Material Not	Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch 130000 Pounds Per Square Inch Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Quantity:	2
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Round Longitudinal Hole Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	40
Minimum Yield Strength: Hole Configuration Style: Round Longitudinal Hole Material: Steel Overall Material Document And Classification: Gef Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hole Configuration Style: Material: Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Configuration Style:	Round Longitudinal Hole
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unc	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unc

How to Order

Order this socket head screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.