

## P/N MS24677-9

## **Description**

length: 5/8", thread: 6-32, socket head screw - alloy steel drilled head

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS246779
Minimum Qty (MOQ): 10

NSN: 5305-00-954-8944

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



# P/N MS24677-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.533 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.595 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Hole Diameter:	0.033 Inches Minimum And 0.039 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-9">https://military-fasteners.com/screws/socket+head+cap+screws/MS24677-9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.