

P/N MS24678-16

Military-Fasteners.com

Description

Fastener Length: 1-1/2", Hole Diameter: 3/64", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	MS2467816
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-951-3395
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24678-16 Specifications

Thread Direction:Right-handThread Direction:Right-handFastener Length:0.875 Inches MinimumFastener Length:1.500 Inches NominalHead Style:Flat ChamferHead Diameter:0.303 Inches Minimum And 0.312 Inches MaximumHole Diameter:0.044 Inches Minimum And 0.190 Inches MaximumHole Diameter:0.044 Inches Minimum And 0.050 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.190 InchesWidth Across Flats:0.190 InchesHole Quantity:6Hole Quantity:1000 Pounds Per Square InchThread Quantity Per Inch:32Minimum Yield Strength:10000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial:Steel OverallMaterial:Gefeed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall		-
Thread Length:0.875 Inches MinimumFastener Length:1.500 Inches NominalHead Style:Flat ChamferHead Diameter:0.303 Inches Minimum And 0.312 Inches MaximumHead Height:0.303 Inches Minimum And 0.312 Inches MaximumHole Diameter:0.044 Inches Minimum And 0.050 Inches MaximumNominal Thread Diameter:0.044 Inches Minimum And 0.050 Inches MaximumNominal Thread Diameter:0.190 InchesWidth Across Flats:0.190 InchesMole Diameter:0.155 Inches Minimum And 0.159 Inches MaximumHole Quantity:6Hole Type:DiriledThread Quantity Per Inch:32Minimum Teisle Strength:160000 Pounds Per Square InchHord Configuration Style:Round Longtunal HoleHole Configuration Style:Round Longtunal HoleMaterial:Steel OverallMaterial:Ger Stat Single Material Response OverallStarface Treatment:Cadmium Overall And Chromate Overall	Thread Class:	3a
Fastener Length:1.500 Inches NominalHead Style:Flat ChamferHead Diameter:0.303 Inches Minimum And 0.312 Inches MaximumHead Height:0.185 Inches Minimum And 0.190 Inches MaximumHole Diameter:0.044 Inches Minimum And 0.050 Inches MaximumInternal Drive Style:NexagonNominal Thread Diameter:0.190 Inches Minimum And 0.159 Inches MaximumWidth Across Flats:0.156 Inches Minimum And 0.159 Inches MaximumHole Quantity:6Hole Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHoless Rating:0.3000 Pounds Per Square InchMinimum Yield Strength:30000 Pounds Per Square InchHole Configuration Style:Nound Longitudinal HoleMaterial Document And Classification:6Fed Std Single Material Response OverallMaterial Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Direction:	Right-hand
Head Style:Flat ChamferHead Diameter:0.303 Inches Minimum And 0.312 Inches MaximumHead Height:0.185 Inches Minimum And 0.190 Inches MaximumHole Diameter:0.044 Inches Minimum And 0.050 Inches MaximumInternal Drive Style:No.044 Inches Minimum And 0.050 Inches MaximumNominal Thread Diameter:0.190 InchesWidth Across Flats:0.190 InchesHole Quantity:6Hole Quantity Per Inch:32Thread Quantity Per Inch:30.00 Pounds Per Square InchHole Strength:10000 Pounds Per Square InchHole Corfiguration Style:Sound Longitudinal HoleMaterial Document And Classification:6 Fed Std Single Material Response OverallMaterial Document And Classification:6 Fed Std Single Material Response OverallStrafee Treatment:Scole CoverallMaterial Strength:10000 Poural And Chromate OverallMaterial Document And Classification:6 Fed Std Single Material Response OverallStrafee Treatment:Cadmium Overall And Chromate Response Overall	Thread Length:	0.875 Inches Minimum
Head Diameter:0.303 Inches Minimum And 0.312 Inches MaximumHead Height:0.185 Inches Minimum And 0.190 Inches MaximumHole Diameter:0.044 Inches Minimum And 0.050 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.190 InchesWidth Across Flats:0.156 Inches Minimum And 0.159 Inches MaximumHole Quantity:6Hole Quantity Per Inch:32Minimum Tensile Strength:1000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 3.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial:Ger Statis Response OverallSurface Treatment:Que-y16,ty 2,cl 3 Fed Spec All Treatment Response Overall	Fastener Length:	1.500 Inches Nominal
Head Height:0.185 Inches Minimun And 0.190 Inches MaximumHole Diameter:0.044 Inches Minimun And 0.050 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.190 InchesWidth Across Flats:0.156 Inches Minimun And 0.159 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial:Ge Sted Single Material Response OverallSurface Treatment:Cadmium Overall And Chassification:Surface Treatment Document And Classification:Ge per-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Style:	Flat Chamfer
Hole Diameter:0.044 Inches Minimum And 0.050 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.190 InchesWidth Across Flats:0.156 Inches Minimum And 0.159 Inches MaximumHole Quantity:6Hole Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial:66 Fed Std Single Material Response OverallSurface Treatment Document And Classification:Q-p-416,ty 2, cl 3 Fed Spec All Treatment Responses Overall	Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:HexagonNominal Thread Diameter:0.190 InchesWidth Across Flats:0.156 Inches Minimum And 0.159 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHole Configuration Style:8.0.000 Pounds Per Square InchHole Configuration Style:Steel OverallMaterialSteel OverallMaterial Document And Classification:6.6 Fed Std Single Material Response OverallSurface Treatment:Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Nominal Thread Diameter:0.190 InchesWidth Across Flats:0.156 Inches Minimum And 0.159 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHaterial:Steel OverallMaterial:6Surface Treatment:Cadmium Overall And Chassification:Query-Lift Strength:Gere Studie Material Response OverallSurface Treatment:Cadmium Overall And Chasse Soverall	Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Width Across Flats:0.156 Inches Minimum And 0.159 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Internal Drive Style:	Hexagon
Hole Quantity:6Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Qu-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.190 Inches
Hole Type:DrilledHole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallPound Classification:9q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:32Thread Quantity Per Inch:36.0000 Pounds Per Square InchMinimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQu-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Quantity:	6
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Hardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Stingle Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:9q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	32
Minimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:Round Longitudinal HoleMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Configuration Style:	Round Longitudinal Hole
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator: Unf	Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS24678-16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.