

Description

Fastener Length: 1-3/4", Hole Diameter: 3/64", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8", drilled socket head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2467817 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-995-4673 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS24678-17 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Minimum And 0.937 Inches Maximum |
| Fastener Length: | 1.750 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.303 Inches Minimum And 0.312 Inches Maximum |
| Head Height: | 0.185 Inches Minimum And 0.190 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.156 Inches Minimum And 0.159 Inches Maximum |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Hole Configuration Style: | Round Longitudinal Hole |
| Material: | Steel Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24678-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.