

P/N MS24678-18

Description

Fastener Length: 2-", Hole Diameter: 3/64", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2467818

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-989-6782

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS24678-18 Specifications

Thread Length: 0.875 Inches Minimum Fastener Length: 2.000 Inches Nominal Head Style: Flat Chamfer Head Diameter: 0.303 Inches Minimum And 0.312 Inches Maximum Head Height: 0.855 Inches Minimum And 0.190 Inches Maximum Hole Diameter: 0.050 Inches Minimum And 0.190 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.190 Inches Width Across Flats: 0.156 Inches Minimum And 0.159 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material Document And Classification: Seel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Oq-p-416, type 2 Cl 3 Fed Spec All Treatment Responses Overall	Thread Class:	3a
Fastener Length: 2.000 Inches Nominal Head Style: Flat Chamfer Head Diameter: 0.303 Inches Minimum And 0.312 Inches Maximum Head Height: 0.185 Inches Minimum And 0.190 Inches Maximum Hole Diameter: 0.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.190 Inches Width Across Flats: 0.190 Inches Width Across Flats: 0.196 Inches Minimum And 0.159 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.00 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 100000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: 8ctength: 166 Fed Std Single Material Response Overall Material Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Thread Direction:	Right-hand
Head Style: Head Diameter: Head Diameter: Head Height: Hoel Diameter: Hoel Diameter: Hoel Diameter: Hoel Diameter: Hoes Diameter: Hexagon Nominal Thread Diameter: Width Across Flats: Hole Quantity: Hole Quantity: Hole Quantity Per Inch: Hole Quantity Per Inch: Horead Quantity Per Inch: Horead Quantity Per Inch: Horead Quantity Per Inch: Horead Quantity Per Inch: Hole Group Diameter: Width Across Flats: Hole Quantity Per Inch: Horead Quantity Per Inch: Hor	Thread Length:	0.875 Inches Minimum
Head Diameter: 0.303 Inches Minimum And 0.312 Inches Maximum Head Height: 0.185 Inches Minimum And 0.190 Inches Maximum Hole Diameter: 0.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.190 Inches Width Across Flats: 0.156 Inches Minimum And 0.159 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Nockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: 0cq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Fastener Length:	2.000 Inches Nominal
Head Height: Hole Diameter: O.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: O.190 Inches Width Across Flats: O.156 Inches Minimum And 0.159 Inches Maximum Hole Quantity: Hole Quantity: G Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hoffware Stating: Minimum Yield Strength: Hole Configuration Style: Mole Configuration Style: Material: Material Document And Classification: See Station: G Material Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Head Style:	Flat Chamfer
Hole Diameter: 0.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.190 Inches Width Across Flats: 0.156 Inches Minimum And 0.159 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style: Nominal Thread Diameter: 0.190 Inches Width Across Flats: 0.156 Inches Minimum And 0.159 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 9q-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Nominal Thread Diameter: Width Across Flats: 0.156 Inches Minimum And 0.159 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: Gadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Hole Diameter:	0.050 Inches Nominal
Width Across Flats: Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: Ge Fed Std Single Material Response Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Internal Drive Style:	Hexagon
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.190 Inches
Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Hole Quantity:	6
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Round Internal Hexagon Steel Overall Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	32
Minimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style: Material: Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Hole Configuration Style:	Round Internal Hexagon
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,type 2 Cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24678-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.