

P/N MS24678-2

Description

Fastener Length: 3/8", Hole Diameter: 1/32", Thread: 6-40, Head Width: 7/64", Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS246782

Minimum Qty (MOQ): 10

NSN: 5305-00-058-2072

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS24678-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.295 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Hole Diameter:	0.036 Inches Nominal
Internal Drive Style:	Hexagon
End Item Identification:	W/s:fms-a7 Aircraft; Deck Machinery; Towed Array Handling Equipment; Submarine Auxillary And Miscellaneous Systems; Virginia Class Submarine, Ssn-774; Submarine Ship Control And Navigation Systems; Los Angeles Class Ssn (688); Trident Hull Structure; Submarine Hydraulic Systems
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	4 Type

How to Order

