

## P/N MS24678-21

## **Description**

Fastener Length: 5/8", Hole Diameter: 3/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2467821

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-274-0415

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24678-21 Specifications

Thread Class: 3a	
Thread Direction: Rig	ght-hand
Thread Length: 0.5	524 Inches Minimum And 0.625 Inches Maximum
Fastener Length: 0.5	595 Inches Minimum And 0.625 Inches Maximum
Head Style: Fla	at Chamfer
Head Diameter: 0.3	365 Inches Minimum And 0.375 Inches Maximum
Head Height: 0.2	244 Inches Minimum And 0.250 Inches Maximum
Hole Diameter: 0.0	047 Inches Nominal
Internal Drive Style:	exagon
Nominal Thread Diameter: 0.2	250 Inches
Width Across Flats: 0.1	1875 Inches Minimum And 0.1900 Inches Maximum
Hole Quantity: 3	
Hole Type: Dri	rilled
Thread Quantity Per Inch: 28	3
Minimum Tensile Strength: 170	70000 Pounds Per Square Inch
Hardness Rating: 38.	3.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength: 150	50000 Pounds Per Square Inch
Hole Configuration Style:	ound Internal Hexagon
Material: Ste	eel Overall
Surface Treatment: Cad	admium Overall And Chromate Overall
Surface Treatment Document And Classification: Qq	q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Surface Treatment Document And Classification:  Qq- Thread Series Designator:  Unit	

## **How to Order**

Order this socket head screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS24678-21">https://military-fasteners.com/screws/socket+head+cap+screws/MS24678-21</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.