

## P/N MS24678-22

## **Description**

MS24678-22 Socket Head Cap Screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

NAS1351-4H12P

SKU / Model: MS2467822

Minimum Qty (MOQ): 10

NSN: 5305-00-685-3013

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS24678-22 Specifications

Thread Direction: Right-hand Thread Length: 0.695 Inches Minimum Fastener Length: 0.750 Inches Nominal Head Style: Flat Chamfer Head Dimeter: 0.365 Inches Minimum And 0.375 Inches Maximum Head Height: 0.244 Inches Minimum And 0.250 Inches Maximum Head Height: 0.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Quantity: 2 Hole Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment Document And Classification: 9q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall		
Thread Length: Fastener Length: Pastener	Thread Class:	3a
Fastener Length: 0.750 Inches Nominal Head Style: Flat Chamfer Head Diameter: 0.365 Inches Minimum And 0.375 Inches Maximum Head Height: 0.244 Inches Minimum And 0.250 Inches Maximum Hole Diameter: 0.050 Inches Nominal Hole Diameter: 0.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Hole Quantity: 6. Hole Quantity: 0.188 Inches Minimum And 0.190 Inches Maximum Hole Quantity Per Inch: 28 Minimum Tensile Strength: 1.60000 Pounds Per Square Inch Hardness Rating: 3.0000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: 8.0000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: 8.0000 Pounds Per Square Inch Material Document And Classification: 8.0000 Pounds Per Square Inch Stefe Overall Material Document And Classification: 9.0000 Pounds Per Square Inch Surface Treatment Document And Classification: 9.0000 Pounds Per Square Inch Surface Treatment Response Overall	Thread Direction:	Right-hand
Head Style: Head Diameter: Head Diameter: Head Height: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hoed Diameter: Hexagon  Nominal Thread Diameter: Width Across Flats: Hole Quantity: Hole Quantity: Hole Quantity Per Inch: Hole Quantity Per Inch: Hardens Rating: Hole Offiguration Style: Hole Offiguration Maximum And Offiguration Style: Hole Offiguration Style: Hole Offiguration Maximum Overall And Adam Offiguration Style: Hole Offiguration Maximum Overall And Offiguration Style: Hole Offiguration	Thread Length:	0.695 Inches Minimum
Head Diameter: 0.365 Inches Minimum And 0.375 Inches Maximum Head Height: 0.244 Inches Minimum And 0.250 Inches Maximum Hole Diameter: 0.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Hole Type: Drilled Hole Type: Drilled Hole Type: Drilled Hole Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Tensile Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Q-q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Fastener Length:	0.750 Inches Nominal
Head Height: Hole Diameter: O.50 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: O.250 Inches Width Across Flats: O.188 Inches Minimum And 0.190 Inches Maximum Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 28 Minimum Tensile Strength: Hoffware Stating: Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Material Document And Classification: See Staff See Style Single Material Response Overall Surface Treatment Document And Classification: Q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Head Style:	Flat Chamfer
Hole Diameter: 0.050 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:HexagonNominal Thread Diameter:0.250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:5cel OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:9q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Nominal Thread Diameter:  Width Across Flats:  0.188 Inches Minimum And 0.190 Inches Maximum  Hole Quantity: 6 Hole Type: Drilled  Thread Quantity Per Inch: 28 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Internal Hexagon  Material: Steel Overall  Material Document And Classification: Gadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Hole Diameter:	0.050 Inches Nominal
Width Across Flats:  Hole Quantity: 6 Hole Type: Drilled Thread Quantity Per Inch: 28 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: H30000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: Ge Fed Std Single Material Response Overall Surface Treatment: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Hexagon
Hole Quantity:  Hole Type: Drilled  Thread Quantity Per Inch: 28 Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: Hole Configuration Style: Round Internal Hexagon Material: Steel Overall  Material Document And Classification: Gef Fed Std Single Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Hole Type:  Thread Quantity Per Inch:  Alternative Strength:  Drilled  160000 Pounds Per Square Inch  1600000 Pounds Per Square Inch  160000 Pounds Per Square Inch  1600000 Pounds Per Square Inch  160000 Pounds Per Sq	Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:  Minimum Tensile Strength:  160000 Pounds Per Square Inch  36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall  Minimum Yield Strength:  130000 Pounds Per Square Inch  Round Internal Hexagon  Material:  Steel Overall  Material Document And Classification:  66 Fed Std Single Material Response Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Hole Quantity:	6
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall Minimum Yield Strength: 130000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Hole Type:	Drilled
Hardness Rating:  36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall  Minimum Yield Strength:  130000 Pounds Per Square Inch  Round Internal Hexagon  Steel Overall  Material:  Steel Overall  Material Document And Classification:  66 Fed Std Single Material Response Overall  Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	28
Minimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:  Material:  Material Document And Classification:  Surface Treatment:  Surface Treatment Document And Classification:  Round Internal Hexagon  Steel Overall  66 Fed Std Single Material Response Overall  Cadmium Overall And Chromate Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Hole Configuration Style:	Round Internal Hexagon
Surface Treatment:  Cadmium Overall And Chromate Overall  Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unf

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS24678-22">https://military-fasteners.com/screws/socket+head+cap+screws/MS24678-22</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.