

P/N MS24678-24

Military-Fasteners.com

Description

Fastener Length: 1", Hole Diameter: 1/32", Thread: 1/4-28, Head Width: 3/16", Thread Length: 15/16", MS24678 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS2467824	
Minimum Qty (MOQ):	10	
NSN:	5305-00-206-6599	
ECCN:	EAR99	
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc	



P/N MS24678-24 Specifications

Thread Direction:Righ-handThread Length:0.945 Inches MinimumFastener Length:1.000 Inches NominalHead Style:Flat ChamferHead Diameter:0.365 Inches Minimum And 0.375 Inches MaximumHole Diameter:0.444 Inches Minimum And 0.325 Inches MaximumHole Diameter:0.444 Inches NominalHole Diameter:0.444 Inches NominalNominal Thread Diameter:0.444 Inches NominalNominal Thread Diameter:0.4250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Quantity:16000 Pounds Per Square InchThread Quantity Per Inch:8Minimum Yield Strength:16000 Pounds Per Square InchHole Configuration Style:8.000Material Document And Classification:6 Feed Std Single Material Response OverallMaterial Document And Classification:6 Feed Std Single Material Response OverallSurface Treatment Document And Classification:9 q-p-416,ty 2,cl 3 Fed Spec All Treatment Response Overall		
Thread Length:0.45 Inches MinimumFastener Length:1.000 Inches NominalHead Style:Flat ChamferHead Diameter:0.365 Inches Minimu And 0.375 Inches MaximumHole Diameter:0.244 Inches Minimu And 0.250 Inches MaximumHole Diameter:0.244 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.250 InchesWidth Across Flats:0.250 InchesHole Quantity:6Hole Damiter:0.188 Inches Minimu And 0.190 Inches MaximumHole Quantity:8Minimu Tensile Strength:16000 Pounds Per Square InchMinimum Yield Strength:3000 Pounds Per Square InchHole Configuration Style:Roud Per Square InchMaterial:Gourds Per Square InchMaterial:6 Fed Std Single Material Response OverallMaterial:Gourds Per Square InchMaterial:Gourds Per Square Inch <th>Thread Class:</th> <th>За</th>	Thread Class:	За
Fastener Length:1.000 Inches NominalHead Style:Flat ChamferHead Diameter:0.365 Inches Minimum And 0.375 Inches MaximumHead Height:0.244 Inches NominalHole Diameter:0.044 Inches NominalNominal Thread Diameter:0.044 Inches NominalWidth Across Flats:0.250 InchesWidth Across Flats:0.250 Inches Maximum And 0.190 Inches MaximumHole Quantity:6Hole Quantity Per Inch:0.88 Inches Minimum And 0.190 Inches MaximumThread Quantity Per Inch:0.6000 Pounds Per Square InchHole Strength:160000 Pounds Per Square InchHole Configuration Style:0.000 Rounds Per Square InchMinimum Tensile Strength:130000 Pounds Per Square InchMinimum Tensile Strength:130000 Pounds Per Square InchMinimum Tensile Strength:0.000 Rounds Per Square InchMinimum Tensile Strength:130000 Pounds Per Square InchMinimum Tensile Strength:0.000 Rounds Per Square InchMinimum Tensile Strength:0.000 Rounds Per Square InchMinimum Teild Str	Thread Direction:	Right-hand
Head Style:Flat ChamferHead Diameter:0.365 Inches Minimum And 0.375 Inches MaximumHead Height:0.244 Inches Minimum And 0.250 Inches MaximumHole Diameter:0.044 Inches NominalHole Diameter:0.044 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.250 InchesWidth Across Flats:0.250 InchesHole Quantity:6Hole Quantity:0Hole Style:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHole Configuration Style:30.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMaterial:Steel OverallMaterial:Steel OverallMaterial:Gerd Stingle Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Length:	0.945 Inches Minimum
Head Diameter:0.365 Inches Minimum And 0.375 Inches MaximumHead Height:0.244 Inches Minimum And 0.250 Inches MaximumHole Diameter:0.044 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Quantity Per Inch:0.190 Onches MaximumThread Quantity Per Inch:0.600 Pounds Per Square InchMinimum Tensile Strength:16000 Pounds Per Square InchMinimum Yield Strength:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:RoundMaterial:Steel OverallMaterial:Gerd Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416.ty 2.cl 3 Fed Spec All Treatment Responses Overall	Fastener Length:	1.000 Inches Nominal
Head Height:0.244 Inches Minimum And 0.250 Inches MaximumHole Diameter:0.044 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:0800 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Tensile Strength:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Qup-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Style:	Flat Chamfer
Hole Dameter:0.044 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHole Configuration Style:RoundHole Configuration Style:RoundMaterial:Steel OverallMaterial:Ge Fd Std Single Material Response OverallSurface Treatment:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:HexagonNominal Thread Diameter:0.250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHole Configuration Style:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallHole Configuration Style:Steel OverallMaterialSteel OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Nominal Thread Diameter:0.250 InchesWidth Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Diameter:	0.044 Inches Nominal
Width Across Flats:0.188 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Internal Drive Style:	Hexagon
Hole Quantity:6Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Qu-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.250 Inches
Hole Type:DrilledHole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallPounder Construction:Pounder Style:Surface Treatment Document And Classification:Cadmium Overall And Chromate OverallPounder Construction:Pounder Style:Pounder Construction:Pounder	Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:28Thread Quantity Per Inch:160000 Pounds Per Square InchMinimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQuerp-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Quantity:	6
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:130000 Pounds Per Square InchHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Hardness Rating:36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum OverallMinimum Yield Strength:13000 Pounds Per Square InchHole Configuration Style:RoundMaterial:RoundMaterial Document And Classification:Steel OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Qep-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	28
Minimum Yield Strength:13000 Pounds Per Square InchHole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:RoundMaterial:Steel OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material: Steel Overall Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Yield Strength:	130000 Pounds Per Square Inch
Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hole Configuration Style:	Round
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/MS24678-24</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.