

P/N MS24678-61

Description

Fastener Length: 1-63/64", Hole Diameter: 1/16", Thread: 1/2-20, Head Width: 3/8", Thread Length: 1-1/2

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS2467861

Minimum Qty (MOQ): 2

NSN: 5305-00-346-3130


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS24678-61 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum
Fastener Length:	1.984 Inches Minimum And 2.032 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Hole Diameter:	0.064 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round
Material:	Steel Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24678-61 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.