

**Description**

Fastener Length: 3/16", Thread: 4-40, Thread Length: 1/8", MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS246931B                                 |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-144-8295                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS24693-1B Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 2a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.058 Inches Minimum And 0.139 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.157 Inches Minimum And 0.188 Inches Maximum  |
| <b>Head Style:</b>  | Flat Countersunk   |
| <b>Head Diameter:</b>                                       | 0.191 Inches Minimum And 0.225 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.112 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 40   |
| <b>Minimum Tensile Strength:</b>                            | 55000 Pounds Per Square Inch   |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Screw Material:</b>                                      | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 |
| <b>Screw Material Document And Classification:</b>          | 66 Fed Std All Material Responses  |
| <b>Screw Surface Treatment:</b>                             | Oxide  |
| <b>Screw Surface Treatment Document And Classification:</b> | Mil-c-13924,cl 4 Mil Spec Single Treatment Response                                    |
| <b>Thread Series Designator:</b>                            | Unc  |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type And 3c Style  |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-1B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.