

Description

flat head screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS24693271B |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-622-8630 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24693-271B Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.262 Inches Minimum And 0.355 Inches Maximum |
| Fastener Length: | 0.407 Inches Minimum And 0.438 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.333 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Steel Comp 301 Or Steel Comp 302 Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 309s Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 324 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 385 Or Steel Comp 384 Or Steel Comp 323 |
| Screw Surface Treatment: | Oxide |
| Screw Surface Treatment Document And Classification: | Mil-c-13924,cl 4 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-271B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.