

Description

length: 1/2", thread: 10-32, countersunk, flat head, corrosion resistant steel, black oxide coated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693272B
Minimum Qty (MOQ):	100
NSN:	5305-01-070-2951
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24693-272B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.417 Inches Nominal
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.359 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type II
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66,300 Series Fed Std Single Material Response
Screw Surface Treatment:	Passivate And Oxide
Screw Surface Treatment Document And Classification:	66,300 Series Fed Std Single Treatment Response And Mil-c-13924 Mil Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-272B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.