



★ FASTENERS

Military-Fasteners.com

P/N MS24693-272B

Description

length: 1/2", thread: 10-32, countersunk, flat head, corrosion resistant steel, black oxide coated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS24693272B |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-01-070-2951 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24693-272B Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.417 Inches Nominal |
| Fastener Length: | 0.469 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.359 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type II |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | 66,300 Series Fed Std Single Material Response |
| Screw Surface Treatment: | Passivate And Oxide |
| Screw Surface Treatment Document And Classification: | 66,300 Series Fed Std Single Treatment Response And Mil-c-13924 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-272B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.